Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	ELEGALED REGUI	LATION (EU) 2019/20	D15 with regard to energ	gy labelling of light	
Supplier's name or trade mark: VOLTOLUX					
Supplier's address: Inköp, BAUHAUS & Co KB Box 587 175 26 Järfälla					
Model identifie	er: 2009007C				
Type of light so	urce:				
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS	
Light source cap-type		E27			
(or other electric interface)					
Mains or non-m	nains:	NMLS	Connected light source (CLS):	Nej	
Colour-tuneable	e light source:	Nej	Envelope:	-	
High luminance light source:		Nej			
Anti-glare shield	d:	Nej	Dimmable:	Yes	
Product parameters					
Parameter		Value	Parameter .	Value	
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		4	Energy efficiency class	G	
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700	
On-mode power (P _{on}), expressed in W		4,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
Outer	Height	170	Spectral power	See image	
dimensions without	Width	125	distribution in the	in last page	
without	Depth	125		 Sida 1 / 3	

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity	0,458		
		coordinates (x and y)	0,410		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	85	Survival factor	0,90		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;

