Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	ELEGATED REGUL	-AITON (EU) 2019/2	015 with regard to ener	gy labelling of light		
Supplier's name	or trade mark:	VOLTOLUX				
Supplier's address: Inköp, BAUHAUS & Co KB Box 587 175 26 Järfälla						
Model identifie	r: 2000981C					
Type of light so	urce:					
Lighting technol	ogy used:	LED	Non-directional or directional:	NDLS		
Light source cap-type (or other electric interface)		E27				
Mains or non-m	ains:	NMLS	Connected light source (CLS):	Nej		
Colour-tuneable	light source:	Nej	Envelope:	-		
High luminance light source:		Nej				
Anti-glare shield:		Nej	Dimmable:	Yes		
		Product para		T		
Parameter		Value	Parameter	Value		
		General product p				
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		4	Energy efficiency class	G		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		270 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 200		
On-mode power (P _{on}), expressed in W		4,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer	Height	170	Spectral power	See image		
dimensions without	Width	125	distribution in the	in last page		
without	Depth	125		Sida 1 /		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power		If yes, equivalent power (W)	-			
		Chromaticity	0,506			
		coordinates (x and y)	0,420			
Parameters for LED and OLED light sources:						
R9 colour rendering index	value 84	Survival factor	0,90			
the lumen maintenance fa	ctor 0,96					

(a)'-': not applicable; (b)'-': not applicable;

